

SMR23 Ammonium (NH₄-N) Analyzer

RS485 Communication. All-in-One Compact Housing. Explosive Proof.

The Ammonium (NH₄-N) Analyzer is connected directly via RS485 communication interface, providing simple, reliable, cost-saving process data with remote monitoring, calibration, configuration and diagnostic capabilities. Housing in a robust IP68 proof enclosure, 1500 N tensile strength Kevlar reinforced cable, up to 1.2 km digital data transmission, the transmitter is ideally used in water/wastewater industry.

Advantages

- All-in-One Compact Endosure, Built-in Transmitter and Sensors
- Robust IP68 Water Submersible Protection, Directly Installed in the Field, No Cabinet Required
- Plug & Play, On-line Realtime Measurement
- Ultra Low Power Consumption, Ideal for Outdoor Applications
- 1500 N Tensible Strength Kevlar Reinforced Cable
- Temperature and Potassium Compensation
- Surge Protection for Power and RS485 Communication
- RS485 Digital Communication, Minimize Cabling and Engineering Cost
- Standard Modbus RTU Protocol, Direct Connected with PLC, HMI
- Very Stable Electrodes, without the Need of Frequent Calibration
- Metal Membrane of Electrode to Prevent Scratch
- Electrode is over 12 Months Long Period of Life
- Auto Cleaning wiper, Less Maintenance
- Onboard Memory Allowing Users Easily Calibrate and Configure Sensor at Lab and Distribute to Various Fields and Sites
- AQCFG Software Tool for Data Monitoring, Calibration, Configuration and Diagnosis
- IECEx/ATEX Ex ia IIB T5 Ga Explosive Proof Certification

Applications


Drinking water, water treatment, wastewater, fishery

Measurement Method

The ion selective electrode continuous measurement of nitrate is carried out with specific membrane that is selective of ammoniumion. That membrane creates charge separation between the water surrounded electrode and internal filling solution. The charge is measured as a voltage that changes the concentration in the water adjacent the membrane. Compared with the traditional colorimetric method, there are many advantages such as fast response time, more accurate, easier and no reagents used.

Installation

Submersible, flow through, pipe insertion



Specifications

General	
Output Signal	RS485 (Modbus RTU protocol), 19,200 bps, 8 data bits, no parity, 1 stop bit; 4~20 mA (optional)
Data Resolution	16 bits (0.001% FS)
Surge Protection	1,500 VDC
Power	5~12 VDC, 110 mA
Protection	Polarity, Overload, Short circuit
Safety	CE, FCC
Nitrate	
Type	Ion selective electrode
Measurement Range	0.1~100/1~1,000 mg/L (NH ₄ -N) or 0.1~129/1~1,290 mg/L (NH ₄ ⁺), auto range
Accuracy	±5% measured value ±0.5 mg/L (NH ₄ -N)
Resolution	0.01 mg/L
Repeatability	±3% measured value ±0.5 mg/L (NH ₄ -N)
Operation pH	pH 4~8.5
Operating Pressure	Max. 0.2 Kg/cm ²
Operating Temperature	0~40 °C
Process Flow Rate	0.1~4 m/s
Response Time	2 mins
Calibration Interval	Typical 24 months
Protection	IP68
Electrical Connection	M16X1.5 plug fixed cable, M12 connector, 5 pin
Housing Material	POM
Cable	Kevlar reinforced PUR cable, 1500N tensile strength
Dimensions	ø 60X304 mm
Weight	analyzer: approx. 1.5 Kg ; cable: 80 g/m
Potassium	
Measurement range	0.1~1,000 mg/L
Accuracy	±5% measured value ±0.5 mg/L
Resolution	0.01 mg/L
Repeatability	±3% measured value ±0.5 mg/L
Temperature	
Sensor	Pt1000
Measurement Range	0~40 °C
Accuracy	± 0.1 °C
Resolution	0.01 °C
Repeatability	0.1 °C
pH	
Measurement Range	0~14 pH
Accuracy	± 0.1 pH
Resolution	0.01 pH
Repeatability	± 0.01 pH

Ordering Codes

Ordering Codes

SMR23 - 2 - - - 3 - 0 - 1 - - -

Sensor

Potassium+Temperature _____ 2
 Potassium+Temperature+pH _____ 3

Cable Length (m)

5 _____ 005
 10 _____ 010
 Custom _____ 001~999

Cable Type

PUR _____

Housing

POM _____

Wiper

Built-in _____

Wire Connection

Bare Wire _____ 0
 M12 Connector _____ 1


Explosive Proof

None _____ 0
 Certificated _____ 1

Analog Output

None _____ 0
 4~20 mA _____ 1

Dimensions



All performances are subject to the actual performance of the products sold by the company in the market, and are only applicable to the products of the company's brand sold by the company or its designated distributors. All the above data are from the internal test of Kaifa Water Resources, and the data may be biased due to different test environments. The manufacturer reserves the right to make changes to product performance, specifications, samples or designs without notice. All information has been carefully checked for accuracy. If there is any printing omission or there may be errors in translation, the company will not be responsible for the consequences.
www.aquas.com.tw



AQUAS Inc.
 Taipei Office
 Add : 4F.-2, No. 56, Ln. 321, Yangguang St.,
 Neihu Dist., Taipei City 11491, Taiwan. R.O.C.
 T : +886-2-8797-5358#240
 F : +886-2-2657-8926
service@aquas.com.tw

Taichung Office
 Add : 5F., No. 190, Dadun 14th St., Nantun Dist.,
 Taichung City 408, Taiwan. R.O.C.
 T : +886-4-2326-8307